

## DRM C100RE

SKU: 1011

### DRM C100RE Combination Rolling Mill Features & Benefits

- 'C100' Combination Rolling Mill
- 'R' 4-to-1 Reduction Gearbox
- 'E' Side Extension with Half Round Rolls (4-1.5mm)
- 9 Wire Rolling Grooves 7mm to 1mm
- Maximum Sheet Thickness of 5.5mm
- Roll Diameter 50mm
- Roll Width 100mm (65mm / 35mm)



## PRODUCT DESCRIPTION

The Durston DRM C100RE Rolling Mill features our 4-to-1 Self Lubricating Gearbox giving maximum efficiency when rolling materials up to 5.5mm or wire up to 7mm. The 100mm Precision Hardened Rolls have 9 Square Rolling Grooves ranging from 7mm to 1mm in size and a 65mm Flat Rolling area (total roll width 100mm).

The DRM C100RE also includes side extension rollers with 4 half round profiles:

4mm x 1.25mm,

3mm x 1mm,

2mm x 0.75mm,

and 1.5mm x 0.5mm allowing even more flexibility for professional Jewellery Makers.

Adjust this Rolling Mill with ease using the top mounted wheel calibrated to give precise accuracy. As with all Durston Rolling Mills in the DRM Range, the body is solid cast iron giving ultimate strength, which combined with RC64 induction hardened rolls, ensures a lifetime of rolling with professional results.



#### Additional Resources:

[Click here to download the instruction manual.](#)

[Click here to download the mounting hole diagram.](#)

[Click here to download the product diagram with dimensions.](#)

#### Additional or Replacement Extension Rollers available for this model:

[Extension Roller 8, 6 & 3mm for DRM 100](#)

[Extension Roller 10 & 7mm for DRM 100](#)

[Extension Roller 4, 3, 2 & 1.5mm for DRM 100](#) (Included as standard)

[Extension Roller Plain for DRM 100](#) (Included as standard)

Please read our Rolling Mill FAQs tab for more information.

## ADDITIONAL INFORMATION

|                                  |                                |
|----------------------------------|--------------------------------|
| <b>Weight</b>                    | 28.5 kg                        |
| <b>Dimensions</b>                | 44 × 29 × 44 cm                |
| <b>Product Weight (kg)</b>       | 29KG                           |
| <b>Product Length (mm)</b>       | 360                            |
| <b>Product Width (mm)</b>        | 200                            |
| <b>Product Height (mm)</b>       | 320                            |
| <b>Gearbox</b>                   | <a href="#">4-to-1 gearbox</a> |
| <b>Number of Grooves</b>         | 9                              |
| <b>Max. Sheet Thickness (mm)</b> | <a href="#">5.5</a>            |
| <b>Roller Type</b>               | <a href="#">Combination</a>    |
| <b>Roller diameter (mm)</b>      | 50                             |
| <b>Roller Length (mm)</b>        | <a href="#">100</a>            |
| <b>Side Extensions</b>           | 4, 3, 2, 1.5mm                 |
| <b>Max. wire capacity (mm)</b>   | <a href="#">7mm</a>            |