



# **DRM F100RE**

**SKU:** 1013

# DRM F100RE Rolling Mill Features & Benefits

- 'F100' Designed for rolling flat sheet metal up to 100mm
- 'R' 4-to-1 Reduction Gearbox
- 'E' Side Extension with Half Round Rolls (4-1.5mm)
- Maximum Sheet Thickness of 5.5mm
- Roll Diameter 50mm
- Roll Width 100mm

# **PRODUCT DESCRIPTION**

The Durston DRM F100RE Rolling Mill features our 4-to-1 Reduction Self Lubricating Gearbox giving maximum efficiency when rolling materials up to 5.5mm thick, designed specifically for rolling flat sheet metal up to 100mm.

The DRM F100RE also includes side extension rollers with 4 half round profiles,  $4 \text{mm} \times 1.25 \text{mm}$ ,  $3 \text{mm} \times 1 \text{mm}$ ,  $2 \text{mm} \times 0.75 \text{mm}$ , and  $1.5 \text{mm} \times 0.5 \text{mm}$  giving even more flexibility for professional Jewellery Makers.

Adjust this Rolling Mill with ease using the top mounted wheel, calibrated to give precise accuracy, as with all Durston Rolling Mills in the DRM Range, the body is solid cast iron giving ultimate strength, which combined with RC64 induction hardened rolls ensures a lifetime of rolling with professional results.

#### **Additional Resources:**

Click here to download the instruction manual.

Click here to download the mounting hole diagram.

Click here to download the product diagram with dimensions.



### Additional or Replacement Extension Rollers available for this model:

Extension Roller 8, 6 & 3mm for DRM 100

Extension Roller 10 & 7mm for DRM 100

Extension Roller 4, 3, 2 & 1.5mm for DRM 100 (Included as standard)

Extension Roller Plain for DRM 100 (Included as standard)

Please read our Rolling Mill FAQs tab for more information.

# **ADDITIONAL INFORMATION**

Weight 28.35 kg

**Dimensions**  $44 \times 29 \times 44 \text{ cm}$ 

Product Weight (kg) 29KG

Product Length (mm) 360

Product Width (mm) 200

Product Height (mm) 320

**Gearbox** 4-to-1 gearbox

Max. Sheet Thickness (mm) <u>5.5</u>

Roller Type Flat

Roller diameter (mm) 50

Roller Length (mm) 100

**Side Extensions** 4, 3, 2, 1.5mm