

## DRM ROUND 130RE

**SKU:** 1044

### DRM R130RE Wire Rolling Mill Features & Benefits

- **'R130'** Round Groove / Combination Rolling Mill
- **'R'** 5-to-1 Reduction Gearbox
- **'E'** Side Extension with 4 Half Round Grooves (4 to 1.5mm)
- 10 Round Wire Rolling Grooves (Main Roll)
- Roll Diameter 60mm
- Roll Width 130mm ( 75mm / 55mm)



## PRODUCT DESCRIPTION

The Durston DRM Round 130RE Rolling Mill features our 5-to-1 Self Lubricating Gearbox giving maximum efficiency when rolling flat materials up to 6mm or round wire up to 10mm, the 130mm Precision Hardened Rolls have 10 Round Rolling Grooves ranging from 10mm to 1mm in size and a 75mm Flat Rolling area (total roll width 130mm)

Round Wire Sizes: 1, 2, 2.5, 3, 3.5, 4, 4.5, 5, 5.5 and 6mm

The DRM R130RE also includes side extension rollers with 4 half round profiles, 4mm x 1.25mm, 3mm x 1mm, 2mm x 0.75mm, and 1.5mm x 0.5mm giving even more flexibility for professional Jewellery Makers.

Adjust this Rolling Mill with ease using the top mounted wheel, calibrated to give precise accuracy, as with all Durston Rolling Mills in the DRM Range, the body is solid cast iron giving ultimate strength, which combined with RC64 induction hardened rolls ensures a lifetime of rolling with professional results.

The DRM Round 130RE is a Combination Rolling Mill is designed for flat metals, creating perfect circular forms and and half rounds (using the side extension). More variations are available, please browse the full [DRM Rolling Mill Range](#)



#### Additional Resources:

[Click here to download the instruction manual.](#)

[Click here to download the mounting hole diagram.](#)

[Click here to download the product diagram with dimensions.](#)

#### Additional or Replacement Extension Rollers available for this model:

[Extension Roller 8, 6 & 3mm for DRM 130](#)

[Extension Roller 10 & 7mm for DRM 130](#)

[Extension Roller 4, 3, 2 & 1.5mm for DRM 130](#) (Included as standard)

[Extension Roller Plain for DRM 130](#) (Included as standard)

Please read our Rolling Mill FAQs tab for more information.

## ADDITIONAL INFORMATION

|                                  |                                |
|----------------------------------|--------------------------------|
| <b>Weight</b>                    | 44.65 kg                       |
| <b>Dimensions</b>                | 50 × 32 × 46 cm                |
| <b>Product Weight (kg)</b>       | 45.3KG                         |
| <b>Product Length (mm)</b>       | 410                            |
| <b>Product Width (mm)</b>        | 220                            |
| <b>Product Height (mm)</b>       | 365                            |
| <b>Gearbox</b>                   | <a href="#">5-to-1 gearbox</a> |
| <b>Number of Grooves</b>         | 10                             |
| <b>Max. Sheet Thickness (mm)</b> | <a href="#">6</a>              |
| <b>Roller Type</b>               | <a href="#">Round</a>          |
| <b>Roller diameter (mm)</b>      | 60                             |
| <b>Roller Length (mm)</b>        | <a href="#">130</a>            |
| <b>Side Extensions</b>           | 4, 3, 2, 1.5mm                 |
| <b>Max. wire capacity (mm)</b>   | <a href="#">10mm</a>           |