

FSM200 DOUBLE

SKU: 1083



Powered Rolling Mill - FSM 200 - Double Sided from Durston Tools. Durston Tools is the market leader in precision rolling mills and no wonder; the FSM 200 Double-Sided Power Mill is constructed from cast iron for optimal strength and rigidity. The mill is available in two-speed configurations; fixed speed and variable speed. There is also a computer control panel which offers more information such as roll speed, pressure, oil indicator and light work. This mill is floor standing and offers automatic lubrication to roller bearings, 200mm of flat roll area and 24 square grooves.

PRODUCT DESCRIPTION

Durston is the market leader in precision rolling mills and no wonder; the FSM 200 Double-Sided Power Mill is constructed from cast iron for optimal strength and rigidity. The mill is available in two-speed configurations; fixed speed and variable speed. There is also a computer control panel which offers more information such as roll speed, pressure, oil indicator and light work. This mill is floor standing and offers automatic lubrication to roller bearings, 200mm of flat roll area and 24 square grooves. The powerful 5.5 KW motor can provides continuous operation, which is why Durston mills have such a long working life. This versatile package has variable speeds with forward and reverse and a highly efficient, near silent operation. The heavy-duty cast iron gearbox means a smooth delivery of power to create a perfect finish every time. The rolls are specially induction hardened to 64 RC; the right barrel provides a large flat rolling service of 200mm on rollers with a diameter of 110mm to a maximum roll thickness of 35mm, ensuring your rolls last a lifetime. The right-hand barrels are dedicated to square wire forming and offers 24 grooves ranging from 12mm to 1mm. Optional extras include digital roll gap metre and work lights.



ADDITIONAL INFORMATION

Weight	1200 kg
Dimensions	160 × 140 × 170 cm
Product Weight (kg)	1050KG
Product Length (mm)	1520
Product Width (mm)	550
Product Height (mm)	1600
Number of Grooves	24
Max. Sheet Thickness (mm)	35
Roller Type	Combination
Roller diameter (mm)	110
Roller Length (mm)	200
Max. wire capacity (mm)	12mm